

VIP-3/PT/PDM-2/24 - Potential distributors



2903798

<https://www.phoenixcontact.com/sg/products/2903798>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module with push-in connection and two equipotential busbars (P1, P2) for potential distribution, for mounting on NS 35 rails. Module width: 57.1 mm

Commercial data

Item number	2903798
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	*****
Product key	CK2124
Catalog page	Page 579 (C-5-2019)
GTIN	4046356796729
Weight per piece (including packing)	134.1 g
Weight per piece (excluding packing)	134.1 g
Customs tariff number	85369010
Country of origin	US

Technical data

Notes

Type of insulation housing	Polyamide PA non-reinforced
Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.

Product properties

Product type	Potential distributor
Product family	VARIOFACE Professional
Potential connections	Per potential (P1, P2) 2 power/12 distributor terminal blocks

Data management status

Article revision	07
------------------	----

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

Nominal voltage U_N	250 V AC/DC
Max. current carrying capacity per branch	15 A
Max. total current of all branches	30 A (per potential)

Input data

Potential connections	Per potential (P1, P2) 2 power/12 distributor terminal blocks
-----------------------	---

Connection data

Feed-in

Connection method	Push-in connection
Stripping length	15 mm
Number of connections	2
Conductor cross section rigid	0.25 mm ² ... 6 mm ²
Conductor cross section flexible	0.25 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 10

Distribution

Connection method	Push-in connection
Stripping length	8 mm
Number of connections	12
Number of positions	2
Conductor cross section rigid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 2.5 mm ²

VIP-3/PT/PDM-2/24 - Potential distributors



2903798

<https://www.phoenixcontact.com/sg/products/2903798>

Conductor cross section AWG	26 ... 14
-----------------------------	-----------

Dimensions

Dimensional drawing	
Width	57.1 mm
Height	75.5 mm
Depth	63 mm

Material specifications

Color	gray (RAL 7042)
-------	-----------------

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-20 °C ... 50 °C (NOTE: At maximum relative humidity < 90%.)
Ambient temperature (storage/transport)	-20 °C ... 70 °C (NOTE: At maximum relative humidity < 90%.)
Altitude	< 2000 m
Permissible humidity (operation)	90 %
Permissible humidity (storage/transport)	90 %

Standards and regulations

Standards/regulations	EN IEC 61010-2-201
-----------------------	--------------------

Mounting

Mounting type	DIN rail mounting
Mounting position	any

VIP-3/PT/PDM-2/24 - Potential distributors





2903798

<https://www.phoenixcontact.com/sg/products/2903798>


Drawings

Dimensional drawing



P2 .01 .02 .03 .04 .05 .06 .07 .08 .09 ← MIDDLE ROW MARKING

P1 .01 .02 .03 .04 .05 .06 .07 .08 .09 ← BOTTOM ROW MARKING




VIP-3/PT/PDM-2/24 - Potential distributors

2903798

<https://www.phoenixcontact.com/sg/products/2903798>



Circuit diagram



VIP-3/PT/PDM-2/24 - Potential distributors



2903798

<https://www.phoenixcontact.com/sg/products/2903798>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sg/products/2903798>



CSA
Approval ID: 2122203

	cUL Recognized Approval ID: E238705			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Output	250 V	15 A	26 - 14	-
Input	250 V	15 A	24 - 8	-

	UL Recognized Approval ID: E238705			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Output	250 V	15 A	26 - 14	-
Input	250 V	15 A	24 - 8	-

cULus Recognized

VIP-3/PT/PDM-2/24 - Potential distributors



2903798

<https://www.phoenixcontact.com/sg/products/2903798>

Classifications

ECLASS

ECLASS-11.0	27400609
ECLASS-12.0	27400609
ECLASS-13.0	27400609

ETIM

ETIM 9.0	EC001894
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

2903798

<https://www.phoenixcontact.com/sg/products/2903798>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.
105 Eunos Avenue 3, #04-00
Singapore 409836
+65 6228 4900
marketing@phoenixcontact.com.sg