

AGK PT 8X6/M10 GNYE - Pick-off terminal block




1083236

<https://www.phoenixcontact.com/sg/products/1083236>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Pick-off terminal block, nom. voltage: 1000 V, nominal current: 41 A, number of connections: 9, connection method: Push-in connection, 1 level, Rated cross section: 6 mm², cross section: 0.5 mm² - 10 mm², Bolt connection, 1 level, mounting type: on base element, color: green/yellow



Your advantages

- The fully insulated, optionally used pick-off terminal block enables voltage pick-off
- Large-surface marking

Commercial data

Item number	1083236
Packing unit	10 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Sales key	*****
Product key	BE2ZWX
Catalog page	Page 119 (C-1-2019)
GTIN	4055626817828
Weight per piece (including packing)	67.4 g
Weight per piece (excluding packing)	62.2 g
Customs tariff number	85369010
Country of origin	CN

AGK PT 8X6/M10 GNYE - Pick-off terminal block



1083236

<https://www.phoenixcontact.com/sg/products/1083236>

Technical data

Product properties

Product type	Pick-off terminal
Number of connections	9
Number of rows	1

Insulation characteristics

Overvoltage category	III
----------------------	-----

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	1.31 W

Connection data

Number of connections per level	9
Nominal cross section	6 mm ²
Rated cross section AWG	10

1 level

Stripping length	10 mm ... 12 mm
Internal cylindrical gage	A5
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.5 mm ² ... 10 mm ²
Cross section AWG	20 ... 8 (converted acc. to IEC)
Conductor cross section flexible	0.5 mm ² ... 6 mm ²
Conductor cross section, flexible [AWG]	20 ... 10 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.5 mm ² ... 6 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 6 mm ²
Conductor cross-section flexible (2 conductors with the same cross-section, with TWIN ferrule and plastic sleeve)	0.5 mm ² ... 1.5 mm ²
Nominal current	41 A
Maximum load current	57 A
Maximum total current	106 A (Bolt connection)
Nominal voltage	1000 V
Nominal cross section	6 mm ²

1 level

Screw thread	M10
Note	Connection bolts
Tightening torque	10 ... 20 Nm
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section flexible	6 mm ² ... 120 mm ²
Conductor cross section, flexible [AWG]	10 ... 250 kcmil (converted acc. to IEC)
Nominal current	41 A

AGK PT 8X6/M10 GNYE - Pick-off terminal block



1083236

<https://www.phoenixcontact.com/sg/products/1083236>

Cable lug connection

Cross section range AWG	(converted acc. to IEC)
Hole diameter	10.4 mm
Width	32 mm
Bolt diameter	10 mm
Screw thread	M10

Dimensions

Width	31 mm
Height	72.6 mm
Depth	32.3 mm
Hole diameter	10.4 mm

Material specifications

Color	green-yellow
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
	IEC 60947-7-1

Mounting

Mounting type	on base element
---------------	-----------------

AGK PT 8X6/M10 GNYE - Pick-off terminal block



1083236

<https://www.phoenixcontact.com/sg/products/1083236>

Drawings

Circuit diagram



AGK PT 8X6/M10 GNYE - Pick-off terminal block



1083236

<https://www.phoenixcontact.com/sg/products/1083236>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sg/products/1083236>

DNV

Approval ID: TAE000037B



CSA

Approval ID: 158887

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B	1000 V	-	20 - 8	-
Use group C	1000 V	-	20 - 8	-



EAC

Approval ID: RU C-DE.BL08.B.00644



cULus Recognized

Approval ID: E60425



cULus Recognized

Approval ID: E60425

AGK PT 8X6/M10 GNYE - Pick-off terminal block



1083236

<https://www.phoenixcontact.com/sg/products/1083236>

Classifications

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250308

ETIM

ETIM 9.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

AGK PT 8X6/M10 GNYE - Pick-off terminal block



1083236

<https://www.phoenixcontact.com/sg/products/1083236>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.
105 Eunos Avenue 3, #04-00
Singapore 409836
+65 6228 4900
marketing@phoenixcontact.com.sg