


HV M8/1 NFF - High-current connector



1056837

<https://www.phoenixcontact.com/sg/products/1056837>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



High-current connector, nom. voltage: 1000 V, nominal current: 150 A, number of connections: 1, connection method: Bolt connection, Rated cross section: 50 mm², mounting type: NS 35/7,5, NS 35/15, color: gray

Your advantages

- Comprehensive, supplementary accessories
- Conical washer CS
- HFR nut screw locking

Commercial data

Item number	1056837
Packing unit	25 pc
Minimum order quantity	25 pc
Sales key	*****
Product key	BE4211
GTIN	4055626697840
Weight per piece (including packing)	55.598 g
Weight per piece (excluding packing)	52.861 g
Customs tariff number	85369010
Country of origin	CN

HV M8/1 NFF - High-current connector



1056837

<https://www.phoenixcontact.com/sg/products/1056837>

Technical data

Product properties

Product type	Bolt connection terminal block
Number of connections	1
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	8 kV
Maximum power dissipation for nominal condition	4.73 W

Connection data

Number of connections per level	1
Nominal cross section	50 mm ²
Stripping length	The stripping length depends on the specification provided by the cable lug manufacturer.
Connection in acc. with standard	IEC 60947-7-1
Nominal current	150 A
Maximum load current	150 A
Nominal voltage	1000 V
Nominal cross section	50 mm ²
Connection in acc. with standard	NF F61-017
Maximum total current	150 A
Nominal voltage	1000 V
Nominal cross section	50 mm ²

Cable lug connection DIN 46234:1980-03

Connection in acc. with standard	DIN 46234:1980-03
Cross section	2.5 mm ² ... 50 mm ²
Cross section range AWG	12 ... 2 (converted acc. to IEC)
Hole diameter	8.4 mm
Width	18 mm
Bolt length	30.5 mm
Bolt diameter	8 mm
Screw thread	M8
Tightening torque	14.40 Nm
Connection in acc. with standard	DIN 46235:1983-07
Cross section	16 mm ² ... 35 mm ²
Cross section range AWG	6 ... 2 (converted acc. to IEC)
Hole diameter	8.4 mm

HV M8/1 NFF - High-current connector



1056837

<https://www.phoenixcontact.com/sg/products/1056837>

Width	20 mm
Bolt length	30.5 mm
Bolt diameter	8 mm
Screw thread	M8
Tightening torque	14.40 Nm
Connection in acc. with standard	DIN 46237:1970-07
Cross section	2.5 mm ² ... 6 mm ²
Cross section range AWG	12 ... 8 (converted acc. to IEC)
Hole diameter	8.4 mm
Width	14 mm
Bolt length	30.5 mm
Bolt diameter	8 mm
Screw thread	M8
Tightening torque	14.40 Nm
Connection in acc. with standard	NF F00-363:1995-12-01
Cross section	... 50 mm ²
Additional text	The stripping length is based on the specifications of the cable lug manufacturer.
Cross section range AWG	(converted acc. to IEC)
Bolt diameter	6 mm
Screw thread	M8
Tightening torque	14.40 Nm
Connection in acc. with standard	NF F00-363
Cross section	10 mm ² ... 50 mm ²
Additional text	Release list on request
Cross section range AWG	(converted acc. to IEC)

Dimensions

Width	21 mm
Height	64 mm
Depth	63.5 mm
Depth on NS 35/7,5	66 mm
Depth on NS 35/15	73.5 mm
Bolt length	31.5 mm

Material specifications

Color	gray (RAL 7042)
Flammability rating according to UL 94	V0
Insulating material group	I
Static insulating material application in cold	-60 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3

HV M8/1 NFF - High-current connector



1056837

<https://www.phoenixcontact.com/sg/products/1056837>

Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Environmental and real-life conditions

Oscillation/broadband noise

Specification	IEC 61373:2010-05
Spectrum	Service life test category 2, bogie-mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$
ASD level	$6.12 \text{ (m/s}^2\text{)}^2\text{/Hz}$
Acceleration	30.6 m/s^2
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Specification	IEC 61373:2010-05
Pulse shape	Half-sine
Acceleration	300 m/s^2
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
	NF F61-017

Mounting

Mounting type	NS 35/7,5
---------------	-----------

HV M8/1 NFF - High-current connector



1056837

<https://www.phoenixcontact.com/sg/products/1056837>

	NS 35/15
--	----------

HV M8/1 NFF - High-current connector



1056837

<https://www.phoenixcontact.com/sg/products/1056837>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sg/products/1056837>



cULus Recognized
Approval ID: E60425



CSA
Approval ID: 13631

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group C				
	1000 V	150 A	14 - 1/0	-



cULus Recognized
Approval ID: E60425

HV M8/1 NFF - High-current connector



1056837

<https://www.phoenixcontact.com/sg/products/1056837>

Classifications

ECLASS

ECLASS-11.0	27141120
ECLASS-13.0	27250101

ETIM

ETIM 9.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

HV M8/1 NFF - High-current connector



1056837

<https://www.phoenixcontact.com/sg/products/1056837>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.

105 Eunos Avenue 3, #04-00

Singapore 409836

+65 6228 4900

marketing@phoenixcontact.com.sg