

SIMATIC ET 200SP, TM Pulse 2x24V PWM and pulse output 2 channels 2 A for proportional valves and DC motors



General information	
Product type designation	TM Pulse 2x24 V
Firmware version	V1.0
<ul style="list-style-type: none"> FW update possible 	Yes
usable BaseUnits	BU type B1
Color code for module-specific color identification plate	CC40
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M 0
<ul style="list-style-type: none"> Isochronous mode 	Yes
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version 	V13 SP1 + HSP
<ul style="list-style-type: none"> STEP 7 configurable/integrated as of version 	V5.5 SP4 and higher
<ul style="list-style-type: none"> PROFIBUS as of GSD version/GSD revision 	GSD Revision 5
<ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision 	GSDML V2.31
Supply voltage	
Load voltage L+	

• Rated value (DC)	24 V
• permissible range, lower limit (DC)	19.2 V
• permissible range, upper limit (DC)	28.8 V
• Short-circuit protection	Yes
• Reverse polarity protection	Yes; against destruction

Input current

Current consumption, max.	70 mA; without load
---------------------------	---------------------

Encoder supply

Number of outputs	2; A common 24V encoder supply for both channels
-------------------	--

24 V encoder supply

• 24 V	Yes; L+ (-0.8 V)
• Short-circuit protection	Yes; per module, electronic
• Output current, max.	300 mA

Power loss

Power loss, typ.	1.7 W
------------------	-------

Address area

Address space per module

• Inputs	16 byte; 8 per channel
• Outputs	24 byte; 12 per channel

Digital inputs

Number of digital inputs	2; 1 per channel
--------------------------	------------------

Digital inputs, parameterizable	Yes
---------------------------------	-----

Input characteristic curve in accordance with IEC 61131, type 3	Yes
---	-----

Digital input functions, parameterizable

• Freely usable digital input	Yes
• HW enable for digital output	Yes

Input voltage

• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-5 ... +5 V
• for signal "1"	+11 to +30V
• permissible voltage at input, min.	-30 V; -5 V continuous, -30 V brief reverse polarity protection
• permissible voltage at input, max.	30 V

Input current

• for signal "1", typ.	2.5 mA
------------------------	--------

Input delay (for rated value of input voltage)

for standard inputs

— parameterizable	Yes; none / 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms
— at "0" to "1", min.	4 µs; for parameterization "none"

— at "1" to "0", min.

4 μ s; for parameterization "none"

Digital outputs	
Type of digital output	P- and M-switching
Number of digital outputs	2; 1 per channel
Current-sinking	Yes
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes; electronic/thermal
<ul style="list-style-type: none"> • Response threshold, typ. 	6.8 A with Standard output, 2 A with High Speed output
Limitation of inductive shutdown voltage to	-0.8 V
Controlling a digital input	Yes
Accuracy of pulse duration	± 100 ppm ± 0.5 μ s with High Speed output, ± 100 ppm ± 9 μ s with Standard output
minimum pulse duration	1.5 μ s; With High Speed output, 10 μ s with Standard output
Digital output functions, parameterizable	
<ul style="list-style-type: none"> • Freely usable digital output 	Yes
<ul style="list-style-type: none"> • PWM output 	Yes
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — Number, max. 	2; 1 per channel
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — Cycle duration, parameterizable 	Yes; Max. 85 s
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — ON period, min. 	0 %
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — ON period, max. 	100 %
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — Resolution of the duty cycle 	0.0036 %; For S7 analog format, min. 20 ns
<ul style="list-style-type: none"> • Connection of a proportional valve 	Yes
<ul style="list-style-type: none"> • Dithering 	Yes
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — Frequency adjustable 	Yes
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — Amplitude adjustable 	Yes
<ul style="list-style-type: none"> • Current measurement 	Yes
<ul style="list-style-type: none"> • Current control 	Yes
<ul style="list-style-type: none"> • Connection of a DC motor 	Yes
<ul style="list-style-type: none"> • ON-delay 	Yes
<ul style="list-style-type: none"> • OFF-delay 	Yes
<ul style="list-style-type: none"> • Frequency output 	Yes
<ul style="list-style-type: none"> • Pulse train 	Yes
<ul style="list-style-type: none"> • Pulse output 	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> • with resistive load, max. 	2 A
<ul style="list-style-type: none"> • on lamp load, max. 	10 W; 1 W with High Speed output
Load resistance range	
<ul style="list-style-type: none"> • lower limit 	12 Ω ; 240 ohm with High Speed output
<ul style="list-style-type: none"> • upper limit 	12 k Ω
Output voltage	
<ul style="list-style-type: none"> • Type of output voltage 	DC

<ul style="list-style-type: none"> • for signal "0", max. 	1 V
<ul style="list-style-type: none"> • for signal "1", min. 	23.2 V; L+ (-0.8 V)
Output current	
<ul style="list-style-type: none"> • for signal "1" rated value 	2 A; 0.1 A with High Speed output, observe derating
Output delay with resistive load	
<ul style="list-style-type: none"> • "0" to "1", typ. 	0 µs; With High Speed output, 4.5 µs with Standard output
<ul style="list-style-type: none"> • "0" to "1", max. 	0.8 µs; With High Speed output, 9 µs with Standard output
<ul style="list-style-type: none"> • "1" to "0", typ. 	0 µs; With High Speed output, 4.5 µs with Standard output
<ul style="list-style-type: none"> • "1" to "0", max. 	0.8 µs; With High Speed output, 9 µs with Standard output
Parallel switching of two outputs	
<ul style="list-style-type: none"> • for uprating 	Yes
Switching frequency	
<ul style="list-style-type: none"> • with resistive load, max. 	100 kHz; With High Speed output, 10 kHz with standard output
<ul style="list-style-type: none"> • with inductive load, max. 	100 kHz; With High Speed output, 10 kHz with standard output
<ul style="list-style-type: none"> • on lamp load, max. 	10 Hz
Total current of the outputs	
<ul style="list-style-type: none"> • Current per channel, max. 	2 A
<ul style="list-style-type: none"> • Current per group, max. 	4 A
<ul style="list-style-type: none"> • Current per module, max. 	4 A
Isochronous mode	
Bus cycle time (TDP), min.	250 µs; with 1 channel configuration, 375 µs with 2 channel configuration
Jitter, max.	1 µs; typically ±
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes; Parameterizable
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes
Diagnostic messages	
<ul style="list-style-type: none"> • Monitoring the supply voltage 	Yes
<ul style="list-style-type: none"> • Short-circuit 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • Monitoring of the supply voltage (PWR-LED) 	Yes; green PWR LED
<ul style="list-style-type: none"> • Channel status display 	Yes
<ul style="list-style-type: none"> • for module diagnostics 	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
<ul style="list-style-type: none"> • between the channels 	No
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
Isolation	
Isolation tested with	707 V DC (type test)

Ambient conditions

Ambient temperature during operation

- | | |
|---------------------------------|-------------------------|
| • horizontal installation, min. | -30 °C |
| • horizontal installation, max. | 60 °C; Observe derating |
| • vertical installation, min. | -30 °C |
| • vertical installation, max. | 50 °C; Observe derating |

Altitude during operation relating to sea level

- | | |
|---|--|
| • Installation altitude above sea level, max. | 2 000 m; On request: Installation altitudes greater than 2 000 m |
|---|--|

Decentralized operation

to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1200	Yes
to SIMATIC S7-1500	Yes
to standard PROFIBUS master	Yes
to standard PROFINET controller	Yes

Dimensions

Width	20 mm
Height	73 mm
Depth	58 mm

Weights

Weight, approx.	50 g
-----------------	------

last modified: 05/13/2020