

# UK 10,3-CC HESILED N 600 3POL - Fuse modular terminal block



3048632

<https://www.phoenixcontact.com/sg/products/3048632>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: Class CC, nom. voltage: 600 V, nominal current: 30 A, connection method: Screw connection, Rated cross section: 25 mm<sup>2</sup>, cross section: 1.5 mm<sup>2</sup> - 25 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: black

## Your advantages

- Easy to bridge
- Fuse holder for fuses up to 600 V
- For 10 x 38 CC fuse-links in accordance with UL 4248-4
- 3-pos. blocked version
- Quick identification of faulty fuses regardless of the current direction, thanks to LED status indicator

## Commercial data

Item number	3048632
Packing unit	3 pc
Minimum order quantity	3 pc
Sales key	*****
Product key	BE1234
GTIN	4046356116022
Weight per piece (including packing)	156.3 g
Weight per piece (excluding packing)	160 g
Customs tariff number	85369095
Country of origin	DE

# UK 10,3-CC HESILED N 600 3POL - Fuse modular terminal block



3048632

<https://www.phoenixcontact.com/sg/products/3048632>

## Technical data

### Notes

#### Trade restriction

CE note	The products are offered exclusively for export outside the EU and the European Economic Area.
---------	--

### Product properties

Product type	Fuse terminal block
Number of connections	2
Number of rows	1

#### Insulation characteristics

Overvoltage category	III
Degree of pollution	3

### Electrical properties

Fuse type	Glass / ceramics / ...
Rated surge voltage	6 kV
Maximum power dissipation for nominal condition	4 W
Fuse	Class CC
LED voltage range	110 V AC/DC ... 600 V AC/DC

### Input data

LED voltage range	110 V AC/DC ... 600 V AC/DC
-------------------	-----------------------------

### Connection data

Number of connections per level	2
Nominal cross section	25 mm <sup>2</sup>
Screw thread	M5
Tightening torque	2 ... 2.5 Nm
Stripping length	11 mm
Internal cylindrical gage	B6
Conductor cross section rigid	1.5 mm <sup>2</sup> ... 25 mm <sup>2</sup>
Cross section AWG	14 ... 4 (converted acc. to IEC)
Conductor cross section flexible	1.5 mm <sup>2</sup> ... 25 mm <sup>2</sup>
Conductor cross section, flexible [AWG]	14 ... 4 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	1.5 mm <sup>2</sup> ... 16 mm <sup>2</sup>
Flexible conductor cross section (ferrule with plastic sleeve)	1.5 mm <sup>2</sup> ... 16 mm <sup>2</sup>
Cross-section with insertion bridge, rigid	10 mm <sup>2</sup>
Cross-section with insertion bridge, flexible	10 mm <sup>2</sup>
2 conductors with same cross section, solid	1.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>

# UK 10,3-CC HESILED N 600 3POL - Fuse modular terminal block



3048632

<https://www.phoenixcontact.com/sg/products/3048632>

2 conductors with same cross section, flexible	1.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	1.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	1.5 mm <sup>2</sup> ... 10 mm <sup>2</sup>
Nominal current	30 A (The voltage is determined by the fuse or selected LED display)
Maximum load current	30 A (the current and voltage are determined by the fuse)
Nominal voltage	600 V (The voltage is determined by the fuse or selected LED display)
Nominal cross section	25 mm <sup>2</sup>

## Dimensions

Width	54 mm
Height	81 mm
Depth on NS 35/7,5	65.5 mm
Depth on NS 35/15	73 mm

## Material specifications

Color	black (RAL 9005)
Flammability rating according to UL 94	V2
Insulating material group	IIIb
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

## Mechanical properties

### Mechanical data

Open side panel	No
-----------------	----

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-60 °C ... 85 °C (max. short-term operating temperature RTI Elec. )
Ambient temperature (storage/transport)	-25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

## Mounting

Mounting type	NS 35/7,5
	NS 35/15


# UK 10,3-CC HESILED N 600 3POL - Fuse modular terminal block

3048632

<https://www.phoenixcontact.com/sg/products/3048632>

## Drawings

Circuit diagram



# UK 10,3-CC HESILED N 600 3POL - Fuse modular terminal block





3048632


<https://www.phoenixcontact.com/sg/products/3048632>


## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sg/products/3048632>

 <b>CSA</b> Approval ID: 225908				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
	600 V	30 A	18 - 4	-
Multi-conductor connection	600 V	30 A	18 - 6	-

 <b>UL Listed</b> Approval ID: FILE E 244294				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
	600 V	30 A	-	18 - 4
Multi-conductor connection	600 V	30 A	-	18 - 6

 <b>cUL Listed</b> Approval ID: FILE E 244294				
	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $\text{mm}^2$
	600 V	30 A	18 - 4	-
Multi-conductor connection	600 V	30 A	18 - 6	-

 <b>EAC</b> Approval ID: EACKZ 08593				
--	--	--	--	--

<b>cULus Listed</b>				
---------------------	--	--	--	--

# UK 10,3-CC HESILED N 600 3POL - Fuse modular terminal block



3048632

<https://www.phoenixcontact.com/sg/products/3048632>

## Classifications

### ECLASS

ECLASS-11.0	27141116
ECLASS-12.0	27141116
ECLASS-13.0	27250113

### ETIM

ETIM 9.0	EC000899
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# UK 10,3-CC HESILED N 600 3POL - Fuse modular terminal block



3048632

<https://www.phoenixcontact.com/sg/products/3048632>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.  
105 Eunos Avenue 3, #04-00  
Singapore 409836  
+65 6228 4900  
[marketing@phoenixcontact.com.sg](mailto:marketing@phoenixcontact.com.sg)