

UK 10,3-CC HESI A 3POL - Fuse modular terminal block



1045698

<https://www.phoenixcontact.com/sg/products/1045698>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Fuse modular terminal block, fuse type: Glass / ceramics / ..., fuse type: Class CC, nom. voltage: 600 V, nominal current: 30 A, connection method: Screw connection, Rated cross section: 16 mm², cross section: 0.75 mm²- 25 mm², mounting type: NS 35/7,5, NS 35/15, color: black

Commercial data

Item number	1045698
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	BE1234
Catalog page	Page 501 (C-1-2019)
GTIN	4055626639208
Weight per piece (excluding packing)	22.22 g

UK 10,3-CC HESI A 3POL - Fuse modular terminal block



1045698

<https://www.phoenixcontact.com/sg/products/1045698>

Technical data

Product properties

Product type	Fuse terminal block
Number of connections	2
Number of rows	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Fuse type	Glass / ceramics / ...
Rated surge voltage	6 kV
Fuse	Class CC

Connection data

Number of connections per level	2
Nominal cross section	16 mm ²
Rated cross section AWG	6

Level 1 above 1 below 1

Screw thread	M4
Tightening torque	1.5 ... 1.8 Nm
Stripping length	12 mm ... 14 mm
Internal cylindrical gage	A7
Conductor cross section rigid	0.75 mm ² ... 25 mm ²
Cross section AWG	16 ... 3 (converted acc. to IEC)
Conductor cross section flexible	0.75 mm ² ... 25 mm ²
Conductor cross section, flexible [AWG]	18 ... 3 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.75 mm ² ... 16 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.75 mm ² ... 16 mm ²
Cross-section with insertion bridge, rigid	10 mm ²
Cross-section with insertion bridge, flexible	10 mm ²
2 conductors with same cross section, solid	0.75 mm ² ... 10 mm ²
2 conductors with same cross section, flexible	0.75 mm ² ... 10 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.75 mm ² ... 6 mm ²
Nominal current	30 A (the current and voltage are determined by the fuse)
Maximum load current	30 A (the current and voltage are determined by the fuse)
Nominal voltage	600 V (the current and voltage are determined by the fuse)
Nominal cross section	16 mm ²

Dimensions

Width	54 mm
-------	-------

UK 10,3-CC HESI A 3POL - Fuse modular terminal block



1045698

<https://www.phoenixcontact.com/sg/products/1045698>

Material specifications

Color	black
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Mounting

Mounting type	NS 35/7,5
	NS 35/15

UK 10,3-CC HESI A 3POL - Fuse modular terminal block




1045698

<https://www.phoenixcontact.com/sg/products/1045698>

Drawings

Circuit diagram



UK 10,3-CC HESI A 3POL - Fuse modular terminal block



1045698

<https://www.phoenixcontact.com/sg/products/1045698>

Classifications

ECLASS

ECLASS-11.0	27141116
-------------	----------

UNSPSC

UNSPSC 21.0	39121410
-------------	----------

UK 10,3-CC HESI A 3POL - Fuse modular terminal block



1045698

<https://www.phoenixcontact.com/sg/products/1045698>

Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.
105 Eunos Avenue 3, #04-00
Singapore 409836
+65 6228 4900
marketing@phoenixcontact.com.sg