

# EC 25 TR - Europe connectors



3240185

<https://www.phoenixcontact.com/sg/products/3240185>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Polyamide Europe terminal strip, transparent, for connecting solid conductors and stranded conductors with ferrules with a cross section of 10 to 25 mm<sup>2</sup>

## Commercial data

Item number	3240185
Packing unit	10 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Sales key	*****
Product key	BE7321
Catalog page	Page 559 (C-3-2019)
GTIN	4046356457897
Weight per piece (including packing)	117.44 g
Weight per piece (excluding packing)	117.44 g
Customs tariff number	85369010
Country of origin	AT

## Technical data

### Product properties

Product type	Europe connector
Number of positions	12
Pitch	16 mm
Number of connections	24
Number of rows	1

### Electrical properties

Maximum power dissipation for nominal condition	3.26 W
---	--------

### Connection data

Nominal cross section	25 mm <sup>2</sup>
Screw thread	M5
Tightening torque	2 ... 3 Nm
Stripping length	9 mm
Conductor cross section rigid	10 mm <sup>2</sup> ... 25 mm <sup>2</sup>
Cross section AWG	8 ... 4 (converted acc. to IEC)
Conductor cross section flexible	10 mm <sup>2</sup> ... 25 mm <sup>2</sup>
Conductor cross section, flexible [AWG]	8 ... 4 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	4 mm <sup>2</sup> ... 16 mm <sup>2</sup>
Flexible conductor cross section (ferrule with plastic sleeve)	4 mm <sup>2</sup> ... 10 mm <sup>2</sup>
2 conductors with same cross section, solid	4 mm <sup>2</sup> ... 6 mm <sup>2</sup>
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	2.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	1.5 mm <sup>2</sup> ... 6 mm <sup>2</sup>
Nominal current	101 A (with 25 mm <sup>2</sup> conductor cross section)
Maximum load current	101 A (with 25 mm <sup>2</sup> conductor cross section)
Nominal voltage	750 V
Nominal cross section	25 mm <sup>2</sup>

### Dimensions

Width	30 mm
Height	28 mm
Depth	30 mm
Drill hole spacing	16 mm
Pitch	16 mm

### Material specifications

Color	transparent
Flammability rating according to UL 94	V2
Insulating material	PA

# EC 25 TR - Europe connectors



3240185

<https://www.phoenixcontact.com/sg/products/3240185>

## Mechanical properties

### Mechanical data

Open side panel	No
-----------------	----

### Technical data

Drill hole spacing	16 mm
--------------------	-------

## Mounting

Mounting type	direct screw connection
---------------	-------------------------

# EC 25 TR - Europe connectors



3240185

<https://www.phoenixcontact.com/sg/products/3240185>

## Classifications

### ECLASS

ECLASS-11.0	27141106
-------------	----------

### ETIM

ETIM 8.0	EC001284
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# EC 25 TR - Europe connectors



3240185

<https://www.phoenixcontact.com/sg/products/3240185>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	35b0de99-94f9-4167-9418-885122c875c6

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.

105 Eunos Avenue 3, #04-00

Singapore 409836

+65 6228 4900

[marketing@phoenixcontact.com.sg](mailto:marketing@phoenixcontact.com.sg)