

# EC 16 - Europe connectors



3240179

<https://www.phoenixcontact.com/sg/products/3240179>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Polypropylene Europe terminal strip, white, for connecting solid conductors and stranded conductors with and without ferrules with a cross section of 1.5 to 16 mm<sup>2</sup>

## Commercial data

Item number	3240179
Packing unit	10 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Sales key	*****
Product key	BE7321
Catalog page	Page 559 (C-3-2019)
GTIN	4046356457842
Weight per piece (including packing)	74.19 g
Weight per piece (excluding packing)	74.19 g
Customs tariff number	85369010
Country of origin	AT

# EC 16 - Europe connectors



3240179

<https://www.phoenixcontact.com/sg/products/3240179>

## Technical data

### Product properties

Product type	Europe connector
Number of positions	12
Pitch	15 mm
Number of connections	24
Number of rows	1

### Electrical properties

Maximum power dissipation for nominal condition	2.43 W
---	--------

### Connection data

Nominal cross section	16 mm <sup>2</sup>
Screw thread	M4
Tightening torque	1.2 ... 1.5 Nm
Stripping length	8 mm
Conductor cross section rigid	1.5 mm <sup>2</sup> ... 16 mm <sup>2</sup>
Cross section AWG	14 ... 6 (converted acc. to IEC)
Conductor cross section flexible	2.5 mm <sup>2</sup> ... 16 mm <sup>2</sup>
Conductor cross section, flexible [AWG]	14 ... 6 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	2.5 mm <sup>2</sup> ... 10 mm <sup>2</sup>
Flexible conductor cross section (ferrule with plastic sleeve)	2.5 mm <sup>2</sup> ... 10 mm <sup>2</sup>
2 conductors with same cross section, solid	2.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>
2 conductors with same cross section, flexible	2.5 mm <sup>2</sup> ... 4 mm <sup>2</sup>
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	1.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	1 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Nominal current	76 A (with 16 mm <sup>2</sup> conductor cross section)
Maximum load current	76 A (with 16 mm <sup>2</sup> conductor cross section)
Nominal voltage	450 V
Nominal cross section	16 mm <sup>2</sup>

### Dimensions

Width	20.7 mm
Height	25 mm
Depth	20.7 mm
Drill hole spacing	15 mm
Pitch	15 mm

### Material specifications

Color	white
Flammability rating according to UL 94	-

# EC 16 - Europe connectors



3240179

<https://www.phoenixcontact.com/sg/products/3240179>

Insulating material	PP
---------------------	----

## Mechanical properties

### Mechanical data

Open side panel	No
-----------------	----

### Technical data

Drill hole spacing	15 mm
--------------------	-------

## Mounting

Mounting type	direct screw connection
---------------	-------------------------

# EC 16 - Europe connectors

3240179

<https://www.phoenixcontact.com/sg/products/3240179>



## Classifications

### ECLASS

ECLASS-11.0

27141106

### ETIM

ETIM 8.0

EC001284

### UNSPSC

UNSPSC 21.0

39121400

# EC 16 - Europe connectors



3240179

<https://www.phoenixcontact.com/sg/products/3240179>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.

105 Eunos Avenue 3, #04-00

Singapore 409836

+65 6228 4900

[marketing@phoenixcontact.com.sg](mailto:marketing@phoenixcontact.com.sg)