


EC 16 TR - Europe connectors



3240181

<https://www.phoenixcontact.com/sg/products/3240181>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Polyamide Europe terminal strip, transparent, for connecting solid conductors and stranded conductors with ferrules with a cross section of 6 to 16 mm²

Commercial data

Item number	3240181
Packing unit	10 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Sales key	*****
Product key	BE7321
Catalog page	Page 559 (C-3-2019)
GTIN	4046356457866
Weight per piece (including packing)	82.14 g
Weight per piece (excluding packing)	82.14 g
Customs tariff number	85369010
Country of origin	AT

EC 16 TR - Europe connectors



3240181

<https://www.phoenixcontact.com/sg/products/3240181>

Technical data

Product properties

Product type	Europe connector
Number of positions	12
Pitch	15 mm
Number of connections	24
Number of rows	1

Electrical properties

Maximum power dissipation for nominal condition	2.43 W
---	--------

Connection data

Nominal cross section	16 mm ²
Screw thread	M4
Tightening torque	1.2 ... 1.5 Nm
Stripping length	8 mm
Conductor cross section rigid	1.5 mm ² ... 16 mm ²
Cross section AWG	14 ... 6 (converted acc. to IEC)
Conductor cross section flexible	2.5 mm ² ... 16 mm ²
Conductor cross section, flexible [AWG]	14 ... 6 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	1.5 mm ² ... 10 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	1.5 mm ² ... 10 mm ²
2 conductors with same cross section, solid	1.5 mm ² ... 4 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	1.5 mm ² ... 2.5 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.75 mm ² ... 2.5 mm ²
Nominal current	76 A (with 16 mm ² conductor cross section)
Maximum load current	76 A (with 16 mm ² conductor cross section)
Nominal voltage	450 V
Nominal cross section	16 mm ²

Dimensions

Width	25.2 mm
Height	20.8 mm
Depth	25.2 mm
Drill hole spacing	15 mm
Pitch	15 mm

Material specifications

Color	transparent
Flammability rating according to UL 94	V2
Insulating material	PA

EC 16 TR - Europe connectors



3240181

<https://www.phoenixcontact.com/sg/products/3240181>

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Technical data

Drill hole spacing	15 mm
--------------------	-------

Mounting

Mounting type	direct screw connection
---------------	-------------------------

EC 16 TR - Europe connectors





3240181

<https://www.phoenixcontact.com/sg/products/3240181>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sg/products/3240181>

 cUL Recognized Approval ID: FILE E 60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B	300 V	55 A	10 - 6	-
Use group C	300 V	55 A	10 - 6	-
Use group D	300 V	55 A	10 - 6	-

 UL Recognized Approval ID: FILE E 60425				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Use group B	300 V	55 A	10 - 6	-
Use group C	300 V	55 A	10 - 6	-
Use group D	300 V	55 A	10 - 6	-

cULus Recognized

EC 16 TR - Europe connectors



3240181

<https://www.phoenixcontact.com/sg/products/3240181>

Classifications

ECLASS

ECLASS-11.0	27141106
-------------	----------

ETIM

ETIM 8.0	EC001284
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

EC 16 TR - Europe connectors



3240181

<https://www.phoenixcontact.com/sg/products/3240181>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	b8d11979-face-410b-a9af-767b5bd33f5d

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.

105 Eunos Avenue 3, #04-00

Singapore 409836

+65 6228 4900

marketing@phoenixcontact.com.sg