

# MSDBV 2,5-NS 35 OG - Mini feed-through terminal block



3073212

<https://www.phoenixcontact.com/sg/products/3073212>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Mini feed-through terminal block, nom. voltage: 800 V, nominal current: 24 A, number of connections: 4, connection method: Spring-cage connection, 1 level, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.08 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: orange

## Your advantages

- For mounting on NS 35 ... DIN rail
- Space saving thanks to compact design and mounting option on a 15 mm DIN rail
- Clear arrangement thanks to marking of all terminal points
- Easy potential distribution thanks to standardized plug-in bridges

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 3073212                        |
| Packing unit                         | 50 pc                          |
| Minimum order quantity               | 50 pc                          |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | 0161*                          |
| Product key                          | BE2163                         |
| Catalog page                         | Page 302 (C-3-2013)            |
| GTIN                                 | 4046356334228                  |
| Weight per piece (including packing) | 8.484 g                        |
| Weight per piece (excluding packing) | 4.47 g                         |
| Customs tariff number                | 85369010                       |
| Country of origin                    | CN                             |

# MSDBV 2,5-NS 35 OG - Mini feed-through terminal block



3073212

<https://www.phoenixcontact.com/sg/products/3073212>

## Technical data

### Product properties

|                       |                          |
|-----------------------|--------------------------|
| Product type          | Miniature terminal block |
| Number of connections | 4                        |
| Number of rows        | 1                        |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 0.77 W |

### Connection data

|                                 |                     |
|---------------------------------|---------------------|
| Number of connections per level | 2                   |
| Nominal cross section           | 2.5 mm <sup>2</sup> |

#### 1 level

|                                                                                           |                                                       |
|-------------------------------------------------------------------------------------------|-------------------------------------------------------|
| Stripping length                                                                          | 8 mm                                                  |
| Connection in acc. with standard                                                          | IEC 60947-7-1                                         |
| Conductor cross section rigid                                                             | 0.08 mm <sup>2</sup> ... 4 mm <sup>2</sup>            |
| Cross section AWG                                                                         | 28 ... 12 (converted acc. to IEC)                     |
| Conductor cross section flexible                                                          | 0.08 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>          |
| Conductor cross section, flexible [AWG]                                                   | 28 ... 14 (converted acc. to IEC)                     |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>          |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>          |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup>                                   |
| Nominal current                                                                           | 24 A                                                  |
| Maximum load current                                                                      | 30 A (with 4 mm <sup>2</sup> conductor cross section) |
| Nominal voltage                                                                           | 800 V                                                 |
| Nominal cross section                                                                     | 2.5 mm <sup>2</sup>                                   |
| Connection in acc. with standard                                                          | IEC/EN 60079-7                                        |

### Dimensions

|                    |         |
|--------------------|---------|
| Width              | 10.4 mm |
| End cover width    | 4 mm    |
| Height             | 42.7 mm |
| Depth              | 22 mm   |
| Depth on NS 35/7,5 | 32 mm   |
| Depth on NS 35/15  | 39.5 mm |

### Material specifications

# MSDBV 2,5-NS 35 OG - Mini feed-through terminal block



3073212

<https://www.phoenixcontact.com/sg/products/3073212>

|                                                         |                   |
|---------------------------------------------------------|-------------------|
| Color                                                   | orange (RAL 2003) |
| Flammability rating according to UL 94                  | V0                |
| Insulating material group                               | I                 |
| Insulating material                                     | PA                |
| Fire protection for rail vehicles (DIN EN 45545-2) R22  | HL 1 - HL 3       |
| Fire protection for rail vehicles (DIN EN 45545-2) R23  | HL 1 - HL 3       |
| Fire protection for rail vehicles (DIN EN 45545-2) R24  | HL 1 - HL 3       |
| Fire protection for rail vehicles (DIN EN 45545-2) R26  | HL 1 - HL 3       |
| Calorimetric heat release NFPA 130 (ASTM E 1354)        | 28 MJ/kg          |
| Surface flammability NFPA 130 (ASTM E 162)              | passed            |
| Specific optical density of smoke NFPA 130 (ASTM E 662) | passed            |
| Smoke gas toxicity NFPA 130 (SMP 800C)                  | passed            |

## Electrical tests

### Surge voltage test

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Temperature-rise test

|                                                  |                                     |
|--------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test                | Increase in temperature $\leq 45$ K |
| Result                                           | Test passed                         |
| Short-time withstand current 2.5 mm <sup>2</sup> | 0.3 kA                              |
| Short-time withstand current 4 mm <sup>2</sup>   | 0.48 kA                             |
| Result                                           | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 2 kV        |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 32/NS 35 |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                                |                               |
|--------------------------------|-------------------------------|
| Rotation speed                 | 10 (+/- 2) rpm                |
| Revolutions                    | 135                           |
| Conductor cross section/weight | 0.08 mm <sup>2</sup> / 0.1 kg |
|                                | 2.5 mm <sup>2</sup> / 0.7 kg  |

# MSDBV 2,5-NS 35 OG - Mini feed-through terminal block



3073212

<https://www.phoenixcontact.com/sg/products/3073212>

|        |                            |
|--------|----------------------------|
|        | 4 mm <sup>2</sup> / 0.9 kg |
| Result | Test passed                |

## Environmental and real-life conditions

### Aging

|                    |             |
|--------------------|-------------|
| Temperature cycles | 192         |
| Result             | Test passed |

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Oscillation/broadband noise

|                        |                                                |
|------------------------|------------------------------------------------|
| Specification          | DIN EN 50155 (VDE 0115-200):2018-05            |
| Spectrum               | Long life test category 2, bogie-mounted       |
| Frequency              | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level              | 6.12 (m/s <sup>2</sup> )/Hz                    |
| Acceleration           | 3.12g                                          |
| Test duration per axis | 5 h                                            |
| Test directions        | X-, Y- and Z-axis                              |

### Shocks

|                                |                                   |
|--------------------------------|-----------------------------------|
| Pulse shape                    | Half-sine                         |
| Acceleration                   | 30g                               |
| Shock duration                 | 18 ms                             |
| Number of shocks per direction | 3                                 |
| Test directions                | X-, Y- and Z-axis (pos. and neg.) |

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)                                                    |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |                |
|----------------------------------|----------------|
| Connection in acc. with standard | IEC 60947-7-1  |
|                                  | IEC/EN 60079-7 |

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# MSDBV 2,5-NS 35 OG - Mini feed-through terminal block



3073212

<https://www.phoenixcontact.com/sg/products/3073212>

## Drawings

Circuit diagram



# MSDBV 2,5-NS 35 OG - Mini feed-through terminal block



3073212

<https://www.phoenixcontact.com/sg/products/3073212>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sg/products/3073212>

| CSA<br>Approval ID: 13631 |                       |                       |                   |                             |
|---------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                           | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B               | 600 V                 | 20 A                  | 28 - 12           | -                           |
| Use group C               | 600 V                 | 20 A                  | 28 - 12           | -                           |
| Use group D               | 600 V                 | 20 A                  | 28 - 12           | -                           |

| CB<br>IECEE CB Scheme<br>Approval ID: DE1-62820 |                       |                       |                   |                             |
|-------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                 | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                 | 800 V                 | 24 A                  | -                 | 0.2 - 2.5                   |

| EAC<br>Approval ID: RU C-DE.BL08.B.00644 |  |  |  |  |
|------------------------------------------|--|--|--|--|
|------------------------------------------|--|--|--|--|

| VDE approval of drawings<br>Approval ID: 40029769 |                       |                       |                   |                             |
|---------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                   | 800 V                 | 24 A                  | -                 | 0.2 - 2.5                   |

| cULus Recognized<br>Approval ID: E60425 |                       |                       |                   |                             |
|-----------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                         | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                             | 600 V                 | 20 A                  | 28 - 12           | -                           |
| Use group C                             | 600 V                 | 20 A                  | 28 - 12           | -                           |
| Use group D                             | 600 V                 | 5 A                   | 28 - 12           | -                           |

| EAC<br>Approval ID: EACKZ 08593 |  |  |  |  |
|---------------------------------|--|--|--|--|
|---------------------------------|--|--|--|--|

# MSDBV 2,5-NS 35 OG - Mini feed-through terminal block



3073212

<https://www.phoenixcontact.com/sg/products/3073212>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# MSDBV 2,5-NS 35 OG - Mini feed-through terminal block



3073212

<https://www.phoenixcontact.com/sg/products/3073212>

## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### China RoHS

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|                                        | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.  
105 Eunos Avenue 3, #04-00  
Singapore 409836  
+65 6228 4900  
[marketing@phoenixcontact.com.sg](mailto:marketing@phoenixcontact.com.sg)