

# PP-H 6/ 1-M BU - Plug



3061703

<https://www.phoenixcontact.com/sg/products/3061703>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug, for self-assembly, nom. voltage: 1000 V, nominal current: 41 A, number of connections: 1, number of positions: 1, connection method: Push-in connection, 1 level, Rated cross section: 6 mm<sup>2</sup>, cross section: 0.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, color: blue

## Your advantages

- Large-surface labeling option
- The Push-in technology COMBI plugs for self-assembly provide solutions that users can implement themselves
- Tested for railway applications

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3061703             |
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 50 pc               |
| Sales key                            | *****               |
| Product key                          | BE2244              |
| Catalog page                         | Page 352 (C-1-2019) |
| GTIN                                 | 4046356650359       |
| Weight per piece (including packing) | 7.968 g             |
| Weight per piece (excluding packing) | 7.9 g               |
| Customs tariff number                | 85366990            |
| Country of origin                    | PL                  |

## Technical data

### Product properties

|                       |                   |
|-----------------------|-------------------|
| Product type          | Terminal plug     |
| Area of application   | Railway industry  |
|                       | Machine building  |
|                       | Plant engineering |
| Number of positions   | 1                 |
| Pitch                 | 8.2 mm            |
| Number of connections | 1                 |
| Number of rows        | 1                 |
| Potentials            | 1                 |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 1.31 W |

### Connection data

|                                 |       |
|---------------------------------|-------|
| Number of connections per level | 1     |
| Nominal cross section           | 6 mm² |

#### 1 level

|                                                                                                                   |                                           |
|-------------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| Stripping length                                                                                                  | 12 mm                                     |
| Internal cylindrical gage                                                                                         | A5                                        |
| Connection in acc. with standard                                                                                  | IEC 61984                                 |
| Conductor cross section rigid                                                                                     | 0.5 mm² ... 10 mm²                        |
| Cross section AWG                                                                                                 | 20 ... 8 (converted acc. to IEC)          |
| Conductor cross section flexible                                                                                  | 0.5 mm² ... 6 mm²                         |
| Conductor cross section, flexible [AWG]                                                                           | 20 ... 10 (converted acc. to IEC)         |
| Conductor cross-section flexible (ferrule without plastic sleeve)                                                 | 0.5 mm² ... 6 mm²                         |
| Flexible conductor cross section (ferrule with plastic sleeve)                                                    | 0.5 mm² ... 6 mm²                         |
| Conductor cross-section flexible (2 conductors with the same cross-section, with TWIN ferrule and plastic sleeve) | 0.5 mm² ... 1.5 mm²                       |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve                         | 0.5 mm² ... 1.5 mm²                       |
| Nominal current                                                                                                   | 41 A                                      |
| Maximum load current                                                                                              | 41 A (with 6 mm² conductor cross section) |
| Nominal voltage                                                                                                   | 1000 V                                    |
| Nominal cross section                                                                                             | 6 mm²                                     |

1 level Connection cross sections directly pluggable

# PP-H 6/ 1-M BU - Plug



3061703

<https://www.phoenixcontact.com/sg/products/3061703>

|                                                                   |                                          |
|-------------------------------------------------------------------|------------------------------------------|
| Conductor cross section rigid                                     | 1 mm <sup>2</sup> ... 10 mm <sup>2</sup> |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>  |
| Flexible conductor cross section (ferrule with plastic sleeve)    | 1 mm <sup>2</sup> ... 6 mm <sup>2</sup>  |

## Dimensions

|        |         |
|--------|---------|
| Width  | 8.2 mm  |
| Height | 21 mm   |
| Depth  | 49.3 mm |
| Pitch  | 8.2 mm  |

## Material specifications

|                                                                         |                 |
|-------------------------------------------------------------------------|-----------------|
| Color                                                                   | blue (RAL 5015) |
| Flammability rating according to UL 94                                  | V0              |
| Insulating material group                                               | I               |
| Insulating material                                                     | PA              |
| Static insulating material application in cold                          | -60 °C          |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C          |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3     |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg        |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed          |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed          |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed          |

## Mechanical properties

### Mechanical data

|                 |    |
|-----------------|----|
| Open side panel | No |
|-----------------|----|

## Environmental and real-life conditions

### Ambient conditions

|                                          |                                                                           |
|------------------------------------------|---------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C (max. operating temperature see derating curve)                    |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                           |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                           |
| Permissible humidity (operation)         | 20 % ... 90 %                                                             |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                             |

## Standards and regulations

|                                  |           |
|----------------------------------|-----------|
| Connection in acc. with standard | IEC 61984 |
|----------------------------------|-----------|

# PP-H 6/ 1-M BU - Plug



3061703

<https://www.phoenixcontact.com/sg/products/3061703>


## Mounting


### Assembly note

Use of a parallel pressing tool is recommended for easy latching of the COMBI connector and coupling elements for self-assembly

## Drawings

Schematic diagram





Circuit diagram



# PP-H 6/ 1-M BU - Plug



3061703

<https://www.phoenixcontact.com/sg/products/3061703>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/sg/products/3061703>

| CSA<br>Approval ID: 2030668 |                       |                       |                   |                             |
|-----------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                 | 600 V                 | 40 A                  | 20 - 8            | -                           |
| Use group C                 | 600 V                 | 40 A                  | 20 - 8            | -                           |
| Use group D                 | 600 V                 | 5 A                   | 20 - 8            | -                           |

| CB<br>IECEE CB Scheme<br>Approval ID: DE1-64372_B1_B2 |                       |                       |                   |                             |
|-------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                       | 1000 V                | -                     | -                 | -                           |

| cULus<br>cULus Recognized<br>Approval ID: E60425 |  |  |  |  |
|--------------------------------------------------|--|--|--|--|
|--------------------------------------------------|--|--|--|--|

| cULus<br>cULus Recognized<br>Approval ID: E60425 |  |  |  |  |
|--------------------------------------------------|--|--|--|--|
|--------------------------------------------------|--|--|--|--|

| VDE approval of drawings<br>Approval ID: 40043445 |                       |                       |                   |                             |
|---------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                   | 1000 V                | -                     | -                 | 0.5 - 6                     |

| EAC<br>Approval ID: EACKZ 08593 |  |  |  |  |
|---------------------------------|--|--|--|--|
|---------------------------------|--|--|--|--|

# PP-H 6/ 1-M BU - Plug

3061703

<https://www.phoenixcontact.com/sg/products/3061703>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141151 |
| ECLASS-12.0 | 27141151 |
| ECLASS-13.0 | 27250306 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002021 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|



# PP-H 6/ 1-M BU - Plug

3061703

<https://www.phoenixcontact.com/sg/products/3061703>



## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### China RoHS

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|                                        | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT SEA Pte. Ltd.  
105 Eunos Avenue 3, #04-00  
Singapore 409836  
+65 6228 4900  
[marketing@phoenixcontact.com.sg](mailto:marketing@phoenixcontact.com.sg)