

2908214

https://www.phoenixcontact.com/sg/products/2908214

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



ECOR-2 relay base, for industrial relays with four changeover contacts, bolt connection, for mounting on NS 35/7,5

### Commercial data

Item number	2908214
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	****
Product key	DKF313
GTIN	4055626289144
Weight per piece (including packing)	55.07 g
Weight per piece (excluding packing)	50.5 g
Customs tariff number	85366990
Country of origin	CN



2908214

https://www.phoenixcontact.com/sg/products/2908214

### Technical data

## Product properties

Product type	Relay socket
Product family	ESSENTIAL edition

### Electrical properties

Nominal voltage U <sub>N</sub>	250 V AC/DC
Nominal current I <sub>N</sub>	5 A

#### Connection data

#### Input side

Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	2x 0.2 mm² 2.5 mm² (without ferrule)
	2x 0.2 mm <sup>2</sup> 1.5 mm <sup>2</sup> (with ferrule)
Conductor cross section flexible	2x 0.2 mm² 2.5 mm² (without ferrule)
	2x 0.2 mm² 1.5 mm² (with ferrule)

#### Output side

Connection method	Bolt connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	2x 0.2 mm <sup>2</sup> 2.5 mm <sup>2</sup> (without ferrule)
	2x 0.2 mm <sup>2</sup> 1.5 mm <sup>2</sup> (with ferrule)
Conductor cross section flexible	2x 0.2 mm <sup>2</sup> 2.5 mm <sup>2</sup> (without ferrule)
	2x 0.2 mm <sup>2</sup> 1.5 mm <sup>2</sup> (with ferrule)

#### **Dimensions**

Width	29.8 mm
Height	64.9 mm
Depth Retaining bracket	63 mm (ECOR-RHM-2)

### Material specifications

#### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-25 °C 55 °C
Ambient temperature (storage/transport)	-25 °C 55 °C

### Mounting



2908214

https://www.phoenixcontact.com/sg/products/2908214

Mounting type	DIN rail mounting
Mounting position	any



2908214

https://www.phoenixcontact.com/sg/products/2908214

### **Approvals**

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/sg/products/2908214



cUL Recognized

Approval ID: FILE E 113228



**UL Recognized** 

Approval ID: FILE E 113228



EAC

Approval ID: RU C-DE.\*\*08.B.01419



cULus Recognized

Approval ID: E113228



2908214

https://www.phoenixcontact.com/sg/products/2908214

## Classifications

UNSPSC 21.0

_	$\sim$	1 100	١.
_			

	ECLASS-13.0	27371603		
ETIM				
	ETIM 9.0	EC001456		
U	NSPSC			

39122300



2908214

https://www.phoenixcontact.com/sg/products/2908214

## Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT SEA Pte. Ltd. 105 Eunos Avenue 3, #04-00 Singapore 409836 +65 6228 4900 marketing@phoenixcontact.com.sg