

2856265

https://www.phoenixcontact.com/sg/products/2856265

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Base element for protective plug PT with surge voltage device protection for the power supply unit and one 2-wire floating signal circuit, mounting on NS 35/7.5 and NS 35/15, housing width: 17.5 mm

Your advantages

- · Maximum ease of maintenance, thanks to the 2-piece design
- · Easy selection for all possible demands in MCR applications with a complete product portfolio
- · The signal is not influenced during maintenance work, thanks to the impedance-neutral insertion and removal of protective plugs

Commercial data

Item number	2856265
Packing unit	10 pc
Minimum order quantity	1 pc
Sales key	0710*
Product key	CL2111
Catalog page	Page 123 (C-4-2019)
GTIN	4017918819675
Weight per piece (including packing)	52.326 g
Weight per piece (excluding packing)	45.729 g
Customs tariff number	85363010
Country of origin	DE



2856265

https://www.phoenixcontact.com/sg/products/2856265

Technical data

Product properties

Product type	Base element
Product family	PLUGTRAB PT
Туре	DIN rail module, two-section, divisible
Number of positions	2
Surge protection fault message	none
Wire pairs per module	1

Connection data

Connection method	Screw connection
Screw thread	M3
Tightening torque	0.5 Nm
Conductor cross section flexible	0.2 mm² 2.5 mm²
Conductor cross section rigid	0.2 mm² 4 mm²
Conductor cross section AWG	24 12
Connection method	Screw connection
Screw thread	M3
Tightening torque	0.8 Nm
Conductor cross section flexible	0.2 mm² 2.5 mm²
Conductor cross section rigid	0.2 mm² 4 mm²
Conductor cross section AWG	24 12

Dimensions

Dimensional drawing	99 915 1177 1177 1178 1178
Width	17.7 mm
Height	90 mm
Depth	52 mm
Horizontal pitch	1 Div.
Complete module width	17.7 mm
Complete module height	90 mm
Complete module depth	65.5 mm

Material specifications

Color	black (RAL 9005)
	copper color
Flammability rating according to UL 94	V-0



2856265

https://www.phoenixcontact.com/sg/products/2856265

Mechanical properties

Open side panel	No	

Protective circuit

Information technology

Surge protection fault message	none
Surge protection rault message	none

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C 85 °C

Standards and regulations

Standards/specifications	EN 61643-21/A1
Note	2009

Mounting

Mounting type	DIN rail: 35 mm





2856265

https://www.phoenixcontact.com/sg/products/2856265

Drawings

Dimensional drawing





The figure shows the complete module consisting of a base element and connector



2856265

https://www.phoenixcontact.com/sg/products/2856265

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/sg/products/2856265



EAC

Approval ID: EAC-Zulassung



EAC

Approval ID: RU C-DE.*09.B.00169



2856265

https://www.phoenixcontact.com/sg/products/2856265

Classifications

	ECLASS-13.0	27171592	
ETIM			
	ETIM 9.0	EC002497	
UNSPSC			
	UNSPSC 21.0	39121600	



2856265

https://www.phoenixcontact.com/sg/products/2856265

Environmental product compliance

EU RoHS

25 1616			
Fulfills EU RoHS substance requirements	Yes, No exemptions		
China RoHS			
Environment friendly use period (EFUP)	EFUP-E		
	No hazardous substances above the limits		
EU REACH SVHC			
REACH candidate substance (CAS No.)	No substance above 0.1 wt%		

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT SEA Pte. Ltd. 105 Eunos Avenue 3, #04-00 Singapore 409836 +65 6228 4900 marketing@phoenixcontact.com.sg