



Figure similar

*** spare part *** SIMATIC S7-200 CN, Digital I/O EM 223, only for S7-22X CPU, 4 DI/4 DO, 24 V DC this S7-200 CN product only has CE approval

Power loss	
Power loss, typ.	2 W
Digital inputs	
Number of digital inputs	4
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
Input current	
• for signal "1", typ.	4 mA
Digital outputs	
Number of digital outputs	4
Short-circuit protection	No
Limitation of inductive shutdown voltage to	L+ (-48 V)
Output current	
• for signal "1" rated value	750 mA
Dimensions	
Width	46 mm
Height	80 mm
Depth	62 mm
Classifications	

	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	Marine / Shipping

[Manufacturer Declaration](#)



[CCS \(China Classification Society\)](#)

last modified:

8/22/2024 