

SIMATIC S7-1500, Front connector in push-in design, 40-pole for 25 mm wide modules and compact CPUs of the S7-1500, incl. cable tie



General information

Product type designation	Front connector
--------------------------	-----------------

Connection method

Connection I/O signals

- | | |
|----------------------------------|---|
| • Connection method | Push-in terminal |
| • Number of lines per connection | 1; or max. 8x 2 conductors to 1.5 mm ² (in total) in a shared end sleeve and max. 32x 0.75 mm ² single core |

Conductor cross-section in mm²

- | | |
|---|--|
| — Connectable cable cross-sections for massive cables, min. | 0.25 mm ² |
| — Connectable cable cross-sections for massive cables, min. | 1.5 mm ² ; max. 32x 0.75 mm ² , 8x 1.5 mm ² |
| — Connectable cable cross-sections for flexible cables without end sleeve, min. | 0.25 mm ² |
| — Connectable cable cross-sections for flexible cables without end sleeve, max. | 1.5 mm ² ; max. 32x 0.75 mm ² , 8x 1.5 mm ² |
| — Connectable cable cross-sections for flexible cables with end sleeve, min. | 0.25 mm ² |

— Connectable cable cross-sections for flexible cables with end sleeve, max.	1.5 mm ² ; max. 32x 0.75 mm ² , 8x 1.5 mm ²
Conductor cross-section acc. to AWG	
— Connectable cable cross-sections for massive cables, min.	24
— Connectable cable cross-sections for massive cables, min.	16; max. 32x AWG 19, 8x AWG 16
— Connectable cable cross-sections for flexible cables without end sleeve, min.	24
— Connectable cable cross-sections for flexible cables without end sleeve, max.	16; max. 32x AWG 19, 8x AWG 16
— Connectable cable cross-sections for flexible cables with end sleeve, min.	24
— Connectable cable cross-sections for flexible cables with end sleeve, max.	16; max. 32x AWG 19, 8x AWG 16
Wire end processing	
— Stripped length of cables, min.	8 mm
— Stripped length of cables, max.	11 mm
— End sleeve acc. to DIN 46228 without plastic sleeve	Form A, 10 mm long
— End sleeve acc. to DIN 46228 with plastic sleeve	Form E, 8 mm and 10 mm long
Mounting	
— Tool	Screwdriver, conical design, 3 mm to 3.5 mm
Dimensions	
Width	19.8 mm
Height	130.5 mm
Depth	43 mm
Weights	
Weight, approx.	123 g
last modified:	05/13/2020