

SIMATIC DP, Electronics module f. ET200 PRO, 4 AI TC High Feature, TC type B, E, J, K, L, N, R, S,T Voltage +/-80 mV, Channel diagnostics, incl. bus module, Connection module IO 6ES7194-4..00-0AA0 order separately



Figure similar

Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes; against destruction
Input current	
from supply voltage 1L+, max.	34 mA; Typical
from backplane bus 3.3 V DC, max.	20 mA; Typical
Power loss	
Power loss, typ.	0.7 W
Address area	
Address space per module	
• Address space per module, max.	8 byte
Analog inputs	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	20 V
Cycle time (all channels) max.	Number of active channels per module x basic conversion time

Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	
• -80 mV to +80 mV	Yes
— Input resistance (-80 mV to +80 mV)	10 MΩ
Input ranges (rated values), thermocouples	
• Type B	Yes
— Input resistance (Type B)	10 MΩ
• Type E	Yes
— Input resistance (Type E)	10 MΩ
• Type J	Yes
— Input resistance (type J)	10 MΩ
• Type K	Yes
— Input resistance (Type K)	10 MΩ
• Type L	Yes
— Input resistance (Type L)	10 MΩ
• Type N	Yes
— Input resistance (Type N)	10 MΩ
• Type R	Yes
— Input resistance (Type R)	10 MΩ
• Type S	Yes
— Input resistance (Type S)	10 MΩ
• Type T	Yes
— Input resistance (Type T)	10 MΩ
Thermocouple (TC)	
Temperature compensation	
— internal temperature compensation	Yes
— external temperature compensation with compensations socket	Yes
Cable length	
• shielded, max.	30 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	15 bit; + sign
• Integration time (ms)	2,5 / 16,67 / 20 / 100 ms
• Interference voltage suppression for interference frequency f1 in Hz	10 / 50 / 60 / 400 Hz
• Conversion time (per channel)	4.7/19/22/102 ms
Smoothing of measured values	
• parameterizable	Yes

- | | |
|----------------|---------------------|
| • Step: None | Yes; 1x cycle time |
| • Step: low | Yes; 4x cycle time |
| • Step: Medium | Yes; 16x cycle time |
| • Step: High | Yes; 64x cycle time |

Encoder

Connection of signal encoders

- | | |
|---------------------------|-----|
| • for voltage measurement | Yes |
|---------------------------|-----|

Errors/accuracies

Linearity error (relative to input range), (+/-)	0.01 %
Temperature error (relative to input range), (+/-)	0.0004 %/K; Positive temperature
Crosstalk between the inputs, min.	-90 dB; max.
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.01 %

Operational error limit in overall temperature range

- | | |
|---|------------------------------|
| • Voltage, relative to input range, (+/-) | 0.12 %; Positive temperature |
|---|------------------------------|

Basic error limit (operational limit at 25 °C)

- | | |
|---|-------|
| • Voltage, relative to input range, (+/-) | 0.1 % |
|---|-------|

Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency

- | | |
|--|------------------------------------|
| • Series mode interference (peak value of interference < rated value of input range), min. | 42 dB |
| • Common mode interference (USS < 2.5 V), min. | 85 dB; Interference voltage < 10 V |

Interrupts/diagnostics/status information

Diagnostics function	Yes
----------------------	-----

Alarms

- | | |
|----------------------|----------------------|
| • Diagnostic alarm | Yes; Parameterizable |
| • Hardware interrupt | No |

Diagnostic messages

- | | |
|-----------------------------------|-----|
| • Diagnostic information readable | Yes |
| • Wire-break | Yes |
| • Overflow/underflow | Yes |

Diagnostics indication LED

- | | |
|------------------------|-----|
| • Group error SF (red) | Yes |
|------------------------|-----|

Parameter

Measurement type/range	Deactivated/ ± 80 mV/ TC-EL Type T (Cu-CuNi)/ TC-EL Type K (NiCr-Ni)/ TC-EL Type B (PtRh-PtRh)/ TC-EL Type N (NiCrSi-NiSi)/ TC-EL Typ E (NiCr-CuNi)/ TC-EL Type R (PtRh-Pt)/ TC-EL Type S (PtRh-Pt)/ TC-EL Type J (Fe-Cu-Ni)/ TC-EL Type L (Fe-CuNi)
Comparison point	None/internal/RTD(0)/dyn. ref. temp./fix. ref. temp.

Potential separation

Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes

Isolation	
Isolation tested with	707 V DC (type test)

Standards, approvals, certificates	
Suitable for applications according to AMS 2750	Yes; Declaration of Conformity, see online support entry 109757262
Suitable for applications according to CQI-9	Yes; Based on AMS 2750 E

Dimensions	
Width	45 mm
Height	130 mm
Depth	35 mm

Weights	
Weight, approx.	150 g
last modified:	05/09/2020