


PS2 keyboard 19" DE, with trackball, slide-in keyboard for devices with corresponding interface Further information, Quantity and content: see technical data



| General information | |
|--|--|
| Product type designation | PS/2 withdrawable keyboard DEU |
| Control elements | |
| Keyboard fonts | |
| <ul style="list-style-type: none"> • Design • Keyboard assignment • Color of the buttons • Color of the key inscription • Key illumination • Function keys <ul style="list-style-type: none"> — Number of function keys • Number pad • status LED displays <ul style="list-style-type: none"> — for number pad — for Shift keys | Membrane keyboard 84 (Germany (QWERTZ)) light gray dark gray No 12 Yes; Integrated into key layout Yes; Num, Caps, Scroll and Pad Yes Yes |
| Connection type | |
| <ul style="list-style-type: none"> • Bluetooth radio standard • USB • PS/2 • Cable length | No No Yes 1.5 m |
| Frame size/design | |
| <ul style="list-style-type: none"> • Standard • 19" keyboard | Yes; For industrial applications Yes |
| Installation type/mounting | |
| Rack mounting | Yes |
| Front mounting | No |
| Wall mounting/direct mounting | No |
| maximum permissible angle of inclination without external ventilation | 0° |
| Supply voltage | |
| Design of the power supply | via PS/2 |
| Input current | |
| Current consumption (rated value) | 10 mA; Typical |
| Battery | |
| Battery-operated | No; maintenance-free |
| Degree and class of protection | |
| Splashproof | No |
| Standards, approvals, certificates | |
| CE mark | Yes |

| | |
|---|---|
| RoHS conformity | Yes |
| Ambient conditions | |
| Ambient temperature during operation | |
| • min. | 0 °C |
| • max. | 50 °C |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 65 °C |
| Relative humidity | |
| • Operation, max. | 80 %; no condensation |
| • Condensation permissible | No |
| Operating systems | |
| Runs under operating system | |
| • Windows CE | Yes |
| • Windows Vista | Yes |
| • Windows XP | Yes |
| • Windows 7 | Yes |
| • Windows 8 | Yes |
| connection method / header | |
| Connector type | PS/2 |
| Mechanics/material | |
| Material | |
| • Plastic | Yes; Keyboard itself |
| • Sheet steel | Yes; Powder-coated drawer |
| Service life | |
| • Number of operating cycles, keys | 20 000 000; Operations (approx.) |
| Dimensions | |
| Width | 370 mm; Keyboard |
| Height | 20 mm; Keyboard |
| Depth | 138.5 mm; Keyboard |
| Width of the housing front | 485 mm; Keyboard incl. drawer |
| Height of housing front | 45 mm; Keyboard incl. drawer |
| Enclosure diameter | 465 mm; Mounting depth drawer |
| Weights | |
| Weight (without packaging) | 8 000 g; Without accessories |
| Weight (with packaging) | 9 300 g |
| Scope of supply | |
| Delivery quantity in pieces | 1; Keyboard incl. drawer |
| Other | |
| Merchandise | Yes |
| Manufacturer name | ZF Friedrichshafen AG, Cherry GmbH, Electronic Systems |
| Manufacturer's address | Cherrystr., 91275 Auerbach/OPf., Germany |
| Target devices | Suitable for IPC and HMI devices with the corresponding interfaces (see manual) |
| Usable in the following products | |
| • Product 1 | 6AV2124-0GC13-0AX0 |
| • Product 2 | 6AV2124-0QC13-0AX0 |
| last modified: | 11/3/2021  |