

Product type designation

PROFIBUS bus connector, RS485, Fast Connect, without PG socket, 30°

Product description

PROFIBUS bus connector, RS485, Fast Connect, without PG socket, 30°
SIMATIC DP, BUS CONNECTOR FOR PROFIBUS WITH TILTED CABLE OUTLET, MAX.1.5 MBIT/S, INSUL.PIERCING CONN.DEV., 15 X 57,6 X 39,5 MM (WXHxD), W/O LAN TERMINAT.RESIST. AND.PG CONNECTION SOCKET



Suitability for use

For connecting PROFIBUS nodes to the PROFIBUS bus cable

Transmission rate

Transfer rate / with PROFIBUS DP

9.6 kbit/s ... 1.5 Mbit/s

Interfaces

Number of electrical connections

- for PROFIBUS cables
- for network components or terminal equipment

2

1

Type of electrical connection / FastConnect

Yes

Mechanical data

Design of terminating resistor

no integrated terminating resistor

Material / of the enclosure

plastic

Design, dimensions and weight

Width

15 mm

Height

57.6 mm

Depth

39.5 mm

Net weight

46 g

Permitted ambient conditions

Ambient temperature

- during storage
- during transport

-40 ... +70 °C

-40 ... +70 °C

Protection class IP	IP20
Product properties, functions, components / general	
Product property	
• silicon-free	Yes
Product component	
• PG connection socket	No
• strain relief	Yes
Standards, specifications, approvals	
Certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
last modified:	24.04.2015