

Extension Unit box 24" for mounting on all fully IP65-enclosed 16:9 HMI/IPC devices. Deep empty enclosure for the flexible installation of operator controls, (without pre-perforation)



General information	
Product type designation	Extension Unit box 24"
Installation type/mounting	
Mounting	For mounting on a 16:9 HMI / IPC PRO device (lower part)
Mounting type	Screwed joint
Rack mounting	No
Front mounting	No
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
Degree and class of protection	
IP (all-round)	IP65
NEMA (front)	
<ul style="list-style-type: none"> Enclosure Type 4 at the front 	Yes
Standards, approvals, certificates	
RoHS conformity	Yes
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> min. max. 	0 °C 50 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> min. max. 	-20 °C 60 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. 	2 000 m
Relative humidity	
<ul style="list-style-type: none"> Operation, max. 	90 %; no condensation
Mechanics/material	
Material	
<ul style="list-style-type: none"> Aluminum 	Yes; Powder-coated
Enclosure material (front)	
<ul style="list-style-type: none"> Aluminum 	Yes; Covered with black film
Dimensions	
Width	583 mm
Height	99 mm
Depth	112 mm
Weights	
Weight (without packaging)	3.1 kg

Weight (with packaging)	3.3 kg
Scope of supply	
Delivery quantity in pieces	1
Components included	Screws for attachment
Other	
Target devices	PRO devices for support arm (extendable, round tube) and pedestal (extendable, flange below)
last modified:	1/24/2022 