

Extension Unit box 24" portrait for mounting on all fully IP65-enclosed 16:9 HMI/IPC devices. Deep empty enclosure for the flexible installation of operator controls, (without pre-perforation)



General information	
Product type designation	Extension Unit box 24" portrait
Installation type/mounting	
Mounting	For mounting on a 16:9 HMI / IPC PRO device (lower part)
Mounting type	Screwed joint
Rack mounting	No
Front mounting	No
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
Degree and class of protection	
IP (all-round)	IP65
NEMA (front)	
<ul style="list-style-type: none"> <li>Enclosure Type 4 at the front</li> </ul>	Yes
Standards, approvals, certificates	
RoHS conformity	Yes
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	0 °C 50 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	-20 °C 60 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>	2 000 m
Relative humidity	
<ul style="list-style-type: none"> <li>Operation, max.</li> </ul>	90 %; no condensation
Mechanics/material	
Material	
<ul style="list-style-type: none"> <li>Aluminum</li> </ul>	Yes; Powder-coated
Enclosure material (front)	
<ul style="list-style-type: none"> <li>Aluminum</li> </ul>	Yes; Covered with black film
Dimensions	
Width	361 mm
Height	99 mm
Depth	112 mm
Weights	
Weight (without packaging)	2 kg

Weight (with packaging)	2.2 kg
<b>Scope of supply</b>	
Delivery quantity in pieces	1
Components included	Screws for attachment
<b>Other</b>	
Target devices	PRO devices for support arm (extendable, round tube) and pedestal (extendable, flange below)
<b>last modified:</b>	1/24/2022 