

Data sheet for Control Unit Adapter Kit

Article No. : 6SL3255-0BW01-0NA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar

Electrical data

Operating voltage via

the Power Module DC 24 V

Connections¹⁾

Design Pigtail
Cable length 1.5 m
Number of electrical cores 10
Conductor cross-section 0.13 mm² (AWG 26)

Standards

Compliance with standards CE, UL, C-Tick (RCM), TÜV, EAC
CE marking Low-voltage directive 2014/35/EC

Ambient conditions

Ambient temperature during

Operation -10 ... 60 °C (14 ... 140 °F)
Storage -40 ... 70 °C (-40 ... 158 °F)

Relative humidity during

Operation max. 95 %

Mechanical data

Degree of protection IP20 / UL open type

Power Module Interface Adapter

Height 166.78 mm (6.57 in)
Width 27.75 mm (1.09 in)
Depth 36.25 mm (1.43 in)
Weight 240 g (0.53 lb)

Control Unit adapter plate

Height 252.5 mm (9.94 in)
Width 89.2 mm (3.51 in)
Depth 59.5 mm (2.34 in)
Weight 661 g (1.46 lb)

¹⁾The connection cable is connected at one end to the Control Unit adapter plate. The customer has to plug the other end into the Power Module Interface Adapter.