

Data sheet for Line filter

Article No. : 6SL3203-0BE17-7BA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :



Figure similar

Rated data

Input

| | |
|------------------|---------------|
| Number of phases | 3 AC |
| Line voltage | 380 ... 480 V |

Output

| | |
|---------------|--------|
| Rated current | 11.4 A |
|---------------|--------|

Mechanical data

| | |
|----------------------|---------------------|
| Degree of protection | IP20 / UL open type |
| Net weight | 1.75 kg (3.86 lb) |

Dimensions

| | |
|--------|--------------------|
| Width | 73.0 mm (9.35 in) |
| Height | 237.5 mm (7.95 in) |
| Depth | 65.0 mm (2.56 in) |

Connections

Line side

| | |
|-------------------------|---|
| Version | screw-type terminal |
| Conductor cross-section | 1.00 ... 2.50 mm ² (AWG 18 ... AWG 14) |

Load side

| | |
|-------------------------|-------------------------------|
| Version | shielded lead |
| Conductor cross-section | 1.50 mm ² (AWG 16) |
| Cable length | 0.45 m (1.48 ft) |

PE connection

| | |
|---------|--------------------------------|
| Version | On housing with M5 screw studs |
|---------|--------------------------------|